

# BLACK JACK "DIRECT TO BARE METAL" Controlled Flow Epoxy Seam Sealer "Lifetime Warranty"

**Black Jack** has tremendous adhesion and sealing capabilities when applied to both bare metal or over catalyzed two part epoxy or etch primer.

This controlled flow Two part Epoxy seam sealer is designed for door skins and roof channels and many upper trunk seams. Two Mixer nozzles, Working times: 10 minutes. Black color. 7.3 fl. oz. Dual Cartridges

"Go with the Flow"

<b>Controlled Flow Seam Sealer</b>	# CB-J2
Mixer Nozzle	# GTMN
Gun	# GTSU, # GF-21



- Excellent corrosion fighting and "Wet Out" on bare metals.
- Sealer flows into micro spaces.



- Controlled flow, excellent for roof gutters and trunk corners.
- Can be repaired/top coated with polyester compounds!
- No Blistering.



- Controlled flow, allows taped out seams,.
- Excellent for duplicating O.E.M. door skin bead sealer.

#### LAP SHEAR COMPARISON TABLE — Aluminum to Aluminum

PRODUCT	APPLICATION	LAP SHEAR AT FULL CURE
Crest Code Blue	Plastic Repair (Flexible / Semi Rigid)	767 PSI
Crest Red Line	SMC/Plastic Repair (Rigid)	838 PSI
Crest Black Majik	Seam Sealer (Heavy Bodied)	2159 PSI
Crest Black Jack	Seam Sealer (Controlled Flow)	2087 PSI
Crest Thick N Tan	Seam Sealer (Extra Heavy Bodied)	2159 PSI
Crest Metal Gray	Seam Sealer (Heavy Bodied)	2150 PSI
Crest Skinner	Small Panel Bonder - 30 min.	3500 PSI
Crest Panel Bonder	Panel Bonder - 90 min.	3525 PSI
3M 8115	Panel Bonder	3538 PSI
3M 8308	Seam Sealer (Heavy Bodied)	937 PSI
SEM 39747	Panel Adhesive	1525 PSI
Lord Fusor 112B	Panel Adhesive	1570 PSI





All Crest Epoxy Seam Sealers are: "DIRECT TO BARE METAL" Each comes with a written, "Lifetime Warranty"



# BLACK MAJIK "DIRECT TO BARE METAL" Heavy Bodied Epoxy Seam Sealer, 2159 PSI "Lifetime Warranty"

Black Majik has tremendous adhesion and sealing capabilities when applied to both bare metal or over catalyzed two part epoxy or etch primer.
This Heavy Bodied Two part Epoxy seam sealer is designed for every day applications where non sag performance is needed and rapid handling is necessary .
A true 10 minute working time seam sealer.
Two Mixer nozzles Working times: 10 minutes. Black color.
7.3 fl. oz. Dual Cartridges
"A real Stand Up seam sealer"

Non Sag Seam Sealer Mixer Nozzle Gun

# CB-M1 # GTMN # GTSU, # GF-21



- Easily duplicate O.E.M. seams.
- Actual 10 minute working time.
- More nozzle life
- Less nozzle waste.



- Excellent **FAST** patch panel bonder.
- Seals and bonds in one application!
- 2159 PSI Lap Shear!





- Heavy body, excellent non-sag.
- Duplicates hood & trunk lid seams,
- interior trunk body and floor seams.
- Will not sag on vertical or inverted surfaces.



#### THICK N TAN "DIRECT TO BARE METAL" EXTRA Heavy Bodied Epoxy Seam Sealer "Lifetime Warranty"

Thick N Tan is approved for bare metal. It has tremendous adhesion and sealing capabilities when applied to both bare metal or over catalyzed two part epoxy or etch primer. This heavy bodied two part epoxy seam sealer is designed for every day applications where non sag performance is needed and rapid handling is necessary . Thick-n-Tan is a higher viscosity product than Black Majik. Therefore, it has even more resistance to sagging and it retains all brush marks or other surface textures. It does not flow.

- Tan Color to match OEM
- Bare Metal Approved
- Non-Sag & Non-Flow
- Retains all brush marks
- Great flexibility
- 10 minute working time
- 30 minute paint time
- Comes with 2 Mixer nozzles.
- 7.3 fl. oz. Dual Cartridge

#### "A real Stand Up seam sealer"

Seam Sealer Mixer Nozzle Gun # CTNT # GTMN # GTSU, # GF-21



METAL GRAY "DIRECT TO BARE METAL" Heavy Bodied Epoxy Seam Sealer, 2150 PSI "Lifetime Warranty"

**Metal Gray** is "Direct to Bare Metal", has a "Life Time "Corrosion Protection" Warranty".

Has tremendous adhesion and sealing capabilities when applied to both bare metal or over catalyzed two part epoxy or etch primer. This Heavy Bodied Two part Epoxy seam sealer is designed to "mimic" the color of metal and aluminum, resulting in faster priming while using less material and saving material cost!

A true 10 minute working time seam sealer.

Duplicates O.E.M.'s Color and Texture

Two Mixer nozzles Working times: 10 minutes. Gray color. 7.3 fl. oz. Dual Cartridges

7.3 oz. Dual Cartridge

# CMG7

Mixer Nozzle Gun # GTMN # GTSU, # GF-21

"Mimics" the color of METAL



SEALERS



# **DURA-SEAM PLUS**

Hybrid Technology Seam Sealer

10 Minute Skin Time, Extremely Fast Strength Build Paintable Immediately Direct-To-Metal Solvent Free, Water Free, Isocyanate Free Tough/Durable/Flexible Gun Grade, Excellent Non-Sag. Can be Applied Vertical and Overhead Easily Tooled – Retains Brush Marks, Compatible with Crest Solvents Wet/Dry Surfaces VOC Compliant, Low Odor

- BONDS: Door skin lap seams Hood panel reinforcements Ground effect facias
- SEALS: Drip rails, Shock towers Seams in Hi-Flex areas Large trunk seams Wheel well area seams
- OTHER APPLICATIONS: General Automotive Seam Sealer Trailer and RV Construction and Roofing Industrial Manufacturing Wall Stone, Landscape Block Adhesive Shower Panels/Mirrors/Countertop/Subfloor Adhesive

10.2 oz. Cart. Gray # CDP Extra Nozzle # WCS





#### MULTI-SEAM HEAVY BODIED - NON SAG Paintable immediately and up to 7 days

### Sprayable Seam Sealer

Designed to reproduce O.E.M. look and color characteristics. Available in Gray, Tan, White and Black. Extremely strong bonding. Permanently flexible and will not shrink or crack! Isocyanate free.

Bare metal approved as well as primed and painted surfaces.



- Paint WET on WET or up to 7 DAYS
- 0% VOCs
- May be applied to Bare Metal or to primer
- Flexible
- Non-Sagging
- High Strength
- Retains patterns and brush marks
- Maybe sprayed, brushed or applied in a bead

10.3 oz. net wt. Cart.	Black	# CMSB
10.3 oz. net wt. Cart.	Tan	# CMST
10.3 oz. net wt. Cart.	Gray	# CMSG
10.3 oz. net wt. Cart.	White	# CMSW



#### **MULTI-SEAM SPRAY GUN**

Spray Gun	# GMSG
Outer Nozzle	# WMSO
Inner Nozzle	# WMSI
Ribbon Nozzle	# GTRA





#### **BRUSHABLE QWIK SEAM**

Formulated to dry through a paint film Skins in 5-10 min., paint immediately upon skinning. Low Odor when applied. Natural off-white color or black Bonds to wet or dry surfaces Excellent bonding to high-solids paints Will not crack, peel or shrink Tools easily. sandable, non-sagging, non-staining Extra tough yet remains permanently flexible

32 oz. Quart	
Natural	# BJN
Black	# BJBQ

#### **DRIP SEAL**

8 oz. Tube	Black	# TJ B
8 oz. Tube	Clear	# TJ C

# **QWIK SEAM**

Tube Grade Formulated to dry through a paint film Skins in 5-10 min., paint immediately upon skinning Natural off-white color Bonds to wet or dry surfaces Excellent bonding to high- solids paints Will not crack, peel or shrink Tools easily. sandable, non-sagging, non-staining Extra tough yet remains permanently flexible

8 oz. Tube Natural # TJN



#### **QWIK SEAM**

Cartridge, Tube Grade & Brushable Formulated to dry through a paint film Skins in 5-10 min., paint immediately upon skinning Natural off-white color or black Bonds to wet or dry surfaces Excellent bonding to high-solids paints Will not crack, peel or shrink. Tools easily. Sandable, non-sagging, non-staining Extra tough yet remains permanently flexible

11 oz. Cart.	Natural	# CJN
11 oz. Cart.	Black	# CJB





# **FLEXI-ROLL**

Sound deadening mat. Designed to replace trunk mat and restore O.E.M. appearance. Very flexible, when heated, melts to conform to any contour. Can be easily trimmed to any size or shape.

3'x 5' Rolled Sheet # XFR



### **FLEXI-SQUARES**

Sound deadening pads. Very flexible, excellent adhesion, paintable, waterproof and duplicates O.E.M. appearance.

12"x12" 6/box #	XFS
-----------------	-----



# CLEAR GUARD SMASH WRAP

The new Smash wrap is a solvent based adhesive which means no more adhesive transfer which means quicker clean up. Clear multi-task self adhering protective sheeting with UV Inhibitors. Excellent for sealing broken glass. Protects paint booths and lights from over spray accumulation. Excellent for covering seats and floors of customers cars. Can be used as a floor runner in your office. Popular as a work bench cover. Great for a weather guard on the inner door panel. The New Smash Wrap is <u>4 mil</u> THICK!

3' x 100'

# ZRSW



# **FLOOR FILM**

The new Floor Film is a Clear multi-task self adhering protective sheeting with UV Inhibitors. Specially designed to help keep the paint booth clean from over spray accumulation. Can be used as a floor runner in your office. Popular as a work

bench cover. Great for a weather guard on the inner door panel. The New Floor film  $\frac{4 \text{ mil}}{2 \text{ mil}}$  thick.

4' x 200' # ZRFF









# SILICONE RUBBER SEALER

Multipurpose silicone rubber. Excellent gasket sealer Heat resistant, Superior oil resistance

Black	# CSSB
Clear	# CSSC
White	# CSSW
	# WCS
	Clear



**BLACK STRIP CAULK** This is some of the best Dum Dum there is.

# XSB



### FAST SET HI-VISCOSITY URETHANE FAST CURE - Structural Windshield Adhesive & Sealant.

This fast set urethane is a "high viscosity" product and does not require . dams or shims to support the glass. Drive away time of 4 hours. CUV is primerless to glass and original urethane sealants. Use urethane primer, Stock # BPV on bare or painted metal..

- Low Conductive: can be used with windshields with electronics (Cameras)
- Excellent seam sealer, Paintable immediately

10.5 OZ. Cart. Black # CUV **Standard Nozzle #WCUV** 

# UNIVERSAL URETHANE PRIMER

Designed for use with SRP Fast Set Urethane, CUV. May be used on metal pinchweld, clear glass, plastic or metal encapsulated glass and glass frit bands. Appling primer to existing urethane is not recommended. Allow 10-15 minutes to dry. Two daubers with each can. Read and follow instructions with primer. # BPV

1.0 oz. Black



**DAUBERS**, 12 PACK # WDU



# **BUTYL TAPE**

#### Multi use adhesive tape

Not as popular as the old days for installing windshields, but it is still a go to for many shop needs.

6S

1/4 x 15' Roll	# RWR1/4S
5/16 x 15' Roll	# RWR5/168



#### **DAM TAPE** Single Sided Adhesive Foam. Allows air to pass thru tape to cure urethane sealers in recommended times.



20' rolls 6 mm x 6 mm

**#RFD6MM**