



HONEY COAT CAVITY & RUST PROOFING

Penetrating formula to seep deep into seams.



360° SPRAY WAND

Quickly get protection where it's needed with a 360° spray wand. Wand can be cleaned with brake cleaner.

Wand # WAHC



BLACK OUT Rubberized Undercoat

Prevents rust
Seals & protects
Sound deadens
High density / heavy duty

20 oz. Black # ABO
Aerosol

RUBBER COAT "PAINTABLE" "THE BEST QUALITY"

- All rubber, no asphalt, no-bleed, rubber undercoat for fender replacements, section repairs, weld joints, rust holes, trunk interiors, lower body surfaces
- Fast drying, paintable, waterproofs, sound deadens and protects. New V.O.C Compliant formula.

With the all New "A1" Abrams Extension Tube

24 oz. Black # ARC

G1

**RUST-PROOFING
PAINTS & SEALERS**



QWIK CLEAR

Time saving and waste reducing aerosol lacquer clear coat. For color match test panels, door jambs, under hood and trunk areas. Other small parts as well. No mixing, no spray gun clean up. Fast dry time with a high gloss. 12 per case.

16 oz. Aerosol

AQC



SPRAY PAINT

This bright white special fast dry lacquer is ideal for auto and truck refinishing. 16 oz. Aerosol. 12 per case.

GMC White # AM-11

This enamel paint is great for recoating diamond plate, truck rims and bumpers. 16 oz. Aerosol. 12 per case.

Dull Aluminum # AM-16



ENGINE ENAMEL SPRAY PAINTS

High quality, fast dry. Smooth even coverage. Heat resistant. 16 oz. Aerosol. 12 per case.

Gloss Black # AM 1
Flat Black # AM 2
Semi Gloss Blk # AM 12

G2

**RUST-PROOFING
 PAINTS & SEALERS**



QWIK SEAM

Tube Grade Formulated to dry through a paint film
 Skins in 5-10 min., paint immediately upon skinning
 Natural off-white color Bonds to wet or dry surfaces
 Excellent bonding to high- solids paints
 Will not crack, peel or shrink Tools easily. sandable, non-sagging,
 non-staining Extra tough yet remains permanently flexible

8 oz. Tube Natural # TJN

DRIP SEAL

8 oz. Tube Black # TJ B
8 oz. Tube Clear # TJ C



BLACK STRIP CAULK # XSB

This is some of the best Dum Dum there is.



BRUSHABLE QWIK SEAM

Formulated to dry through a paint film
 Skins in 5-10 min., paint immediately upon
 skinning. Low Odor when applied.
 Natural off-white color or black
 Bonds to wet or dry surfaces
 Excellent bonding to high-solids paints
 Will not crack, peel or shrink
 Tools easily. sandable, non-sagging, non-staining
 Extra tough yet remains permanently flexible

32 oz. Quart
Natural # BJN
Black # BJBQ

G3

**RUST-PROOFING
 PAINTS & SEALERS**



**LOCTITE RTV
SILICONE GASKET
MAKERS**



**O.E.M. HIGH
PERFORMANCE**

80 ml. / 2.7 oz. Tubes

- GRAY** (-75°F to 626°F) # **L464**
- COPPER** (-75°F to 700°F) # **L466**
- BLACK** (-75°F to 626°F) # **L467**

**SILICONE RUBBER
SEALER**

Multipurpose silicone rubber.
Excellent gasket sealer
Heat resistant, Superior oil resistance

- 10.3 oz. Cart** **Black** # **CSSB**
- 10.3 oz. Cart** **Clear** # **CSSC**
- 10.3 oz. Cart** **White** # **CSSW**

READY GASKET

Specified as OEM on GM, Ford Daimler-Chrysler.
Ready Gasket makes high performance leak proof
gaskets in one minute. Blowout resistant and sensor
safe Temperature Range: -75°F to 450°F
Black, 7 oz. Can # L510



GASKET MAKER 518

Non-corrosive anaerobic for use on
aluminum, iron and steel flanged mating
surfaces.
6 ml. Tube # L395



G4 **RUST-PROOFING
PAINTS & SEALERS**

FAST SET HI-VISCOSITY URETHANE

FAST CURE - Structural Windshield Adhesive & Sealant.

- This fast set urethane is a "high viscosity" product and does not require dams or shims to support the glass.
- Drive away time of 4 hours.
- CSF is primerless to original urethane sealants.
- Use Crest's urethane primer, BPU, on bare or painted metal as well as the perimeter of the glass and encapsulation if present.
- Primer takes all of the "guess-work" out of windshield installation and assures a proper bond that meets OEM specifications and avoids leaks.
- Excellent seam sealer, Paintable immediately!

10.5 OZ. Cart. Black # CSF
 Standard Nozzle # WCSWCSF
 V-Cut Nozzle # WVCUT



DAUBERS, 12 PACK # WDU

UNIVERSAL URETHANE PRIMER

Designed for use with Crest's Fast Set Urethane, CSF. May be used on metal pinchweld, clear glass, plastic or metal encapsulated glass and glass frit bands. Applying primer to existing urethane is not recommended. Allow 10-15 minutes to dry. Two daubers with each can. Read and follow instructions with primer.

1 oz. Black # BPU



DAM TAPE

Single Sided Adhesive Foam.

Allows air to pass thru tape to cure urethane sealers in recommended times.

20' rolls
 6 mm x 6 mm

#RFD6MM





CLEAR SEAL 5 min. CLEAR EPOXY SEAM SEALER

Clear Seal is a revolutionary two-part epoxy adhesive Seam Sealer.

Capable of sealing and curing under water.

The 5 minute working time makes it perfect for applications where time is of the essence. It is semi – Rigid and self leveling. It may be sanded and painted in 30 minutes.

1.7 oz cart. #ZCEC
Nozzle 12 per bag #GMMN
Gun #GCMT2

BUTYL WINDSHIELD RESEALANTS

Seals leaks in windshields, backlites and taillights. Bonds to wet or dry surfaces. Permanently flexible. Compatible with urethane, butyl or other sealants.

RE-SEAL

Heavy Bodied

Non-Sag

11 oz. Cart. # CRB



LEAK-TRACE

- Locates air, dust, water leaks around weatherstripping.
- Spots transmission leaks.
- Leaks show up as the powder is displaced.
- Belongs on every technician's work bench!

12 oz. Aerosol # ATR

G6

**RUST-PROOFING
 PAINTS & SEALERS**